



Don't let the fear of measuring wrong hold up your kitchen upgrade. Follow this simple 3-step checklist to get perfect, factory-precise custom doors every single time.

☐ **STEP 1: Gather Your Tools & Rules**

Before you pull out your tape measure, agree to these three golden rules of custom ordering:

- **Measure to the nearest 1/16th of an inch.** Do not round up or down to the nearest half-inch.
- **Always write dimensions as Width x Height (W x H).** Width is always the horizontal measurement; Height is always vertical.
- **Measure twice.** Write your numbers down, walk away for five minutes, and measure them again to confirm.

☐ **STEP 2: Choose Your Measuring Method**

Choose Method A if you are replacing existing doors. Choose Method B if you are measuring raw cabinet openings.

Method A: Replacing Existing Doors (Easiest)

Measure the exact back-side of your current doors.

- **Width:** Measure across the back of the door from left edge to right edge: _____ inches.
- **Height:** Measure from top edge to bottom edge: _____ inches.

Method B: Measuring the Cabinet Opening (For Overlay Doors)

Measure the inner clear opening of the cabinet box, then add your overlay. **Standard overlay is 1/2 inch on all sides (adds 1 full inch to total W and H).**

- **Opening Width:** _____ inches + 1 inch = **Final Door Width:** _____ inches.
 - **Opening Height:** _____ inches + 1 inch = **Final Door Height:** _____ inches.
 - *Note: For double doors sharing one opening, measure the total opening width, subtract 1/8 inch (for the center gap), divide by 2, and then add your overlay.*
-

☐ STEP 3: The Final Order Verification Table

Fill this out completely before opening our online door configurator.



Cabinet Location (e.g., Sink Base Left)	Qty	Final Width (W)	Final Height (H)	Hinge Holes Needed? (Y/N)
1.				
2.				
3.				
4.				
5.				
6.				